

Appl. No. 09/943,904  
Amdt. dated December 28, 2006  
Reply to Office Action of October 19, 2006

RECEIVED  
CENTRAL FAX CENTER  
DEC 28 2006

7. (previously presented) The method of claim 6 wherein the recovery initiation modules reside in a fault-tolerant firmware block.
8. (original) The method of claim 7 wherein the recovery initiation modules are contained in a 64 kilobyte block of code.
9. (previously presented) The method of claim 1 wherein the recovery of the computing system is necessitated by an event selected from the group consisting of power failure, hardware failure, and security error.
10. (previously presented) A machine-readable medium that provides executable instructions which, when executed by a processor, cause the processor to perform operations comprising:
  - adding a new initiation module to a BIOS firmware of a computing system having an extensible firmware architecture, the BIOS firmware having a plurality of initiation modules including recovery initiation modules for recovery of the computing system and non-recovery modules;
  - automatically evaluating the new initiation module; and
  - designating the new initiation module as a recovery initiation module if new the initiation module is required for the recovery of the computing system.
11. (previously presented) The machine-readable medium of claim 10 wherein the operations further comprise:
  - designating the new initiation module as a recovery initiation module if another recovery initiation module depends upon the new initiation module.
12. (previously presented) The machine-readable medium of claim 10 wherein the operations further comprise executing only recovery initiation modules in an event of a recovery restart.
13. (previously presented) The machine-readable medium of claim 11 wherein the new initiation module is an updated recovery initiation module added to the BIOS firmware to replace an outdated recovery initiation module.

Appl. No. 09/943,904  
Amdt. dated December 28, 2006  
Reply to Office Action of October 19, 2006

14. (previously presented) The machine-readable medium of claim 13 wherein the method further comprise:

automatically evaluating at least one of the recovery initiation modules;  
removing recovery initiation module designation from the at least one of the recovery initiation modules if the designation is solely due to dependence thereon by the outdated recovery initiation module.

15. (original) The machine-readable medium of claim 10 wherein the recovery initiation modules are rendered unalterable.

16. (previously presented) The machine-readable medium of claim 15 wherein the recovery initiation modules reside in a fault-tolerant firmware block.

17. (original) The machine-readable medium of claim 16 wherein the recovery initiation modules are contained in a 64 kilobyte block of code.

18. (previously presented) The machine-readable medium of claim 10 wherein the recovery of the computing system is necessitated by an event selected from the group consisting of power failure, hardware failure, and security error.

19. (currently amended) An apparatus comprising:

a BIOS firmware component of a computing system having an extensible firmware architecture, the BIOS firmware component containing a BIOS firmware ~~of the computing system~~ having a plurality of initiation modules including recovery initiation modules for recovering of the computing system and non-recovery modules; and

an update firmware component containing a firmware update utility to automatically evaluate a new initiation module added to the BIOS firmware and designating the new initiation module as a recovery initiation module if the new initiation module is required for the ~~recovery~~ recovering of the computing system.

20. (previously presented) The apparatus of claim 19 wherein the new initiation module is designated as a recovery initiation module if another recovery initiation module depends upon the new initiation module.

Appl. No. 09/943,904  
Amdt. dated December 28, 2006  
Reply to Office Action of October 19, 2006

21. (previously presented) The apparatus of claim 19 wherein only recovery initiation modules are executed in an event of a recovery restart.
22. (previously presented) The apparatus of claim 20 wherein the new initiation module is an updated recovery initiation module added to the BIOS firmware to replace an outdated recovery initiation module.
23. (previously presented) The apparatus of claim 21 wherein at least one of the recovery initiation modules is automatically evaluated such that if a designation of the at least one of the recovery initiation modules as a recovery initiation module is solely due to dependence thereon by the outdated recovery initiation module, the designation is removed.
24. (original) The apparatus of claim 19 wherein the recovery initiation modules are rendered unalterable.
25. (previously presented) The apparatus of claim 24 wherein the recovery initiation modules reside in a fault-tolerant firmware block.
26. (original) The apparatus of claim 25 wherein the recovery initiation modules are contained in a 64 kilobyte block of code.
27. (previously presented) The apparatus of claim 19 wherein the recovery of the computing system is necessitated by an event selected from the group consisting of power failure, hardware failure, and security error.